



MARKET DATA SPECIFICATION

FIX Message Reference – Fixed Income - Trademate

Contacts

- B3 Support

 produtosrendafixa@b3.com.br

 +55 11 2565-7464

Attention Point

This document is a preliminary version that may change. The structure of data here is to assist B3 clients in the beginning of the development of market data connectivity for the new fixed income platform.

Index

Contacts	1
1 Market Data FIX Message Specification	6
1.1 Message Blocks	6
1.1.1 Message Header (for all messages)	6
1.1.2 Message Trailer (for all messages)	6
1.1.3 Instrument identification block	6
1.2 Session Level Messages	7
1.2.1 Logon (35=A)	7
1.2.2 Logout (35=5)	7
1.2.3 Heartbeat (35=0)	7
1.2.4 TestRequest (35=1)	7
1.2.5 ResendRequest (35=2)	7
1.2.6 Reject (35=3)	8
1.2.7 SequenceReset (35=4)	8
1.3 Application Messages	9
1.3.1 SecurityListRequest (35=x)	9
1.3.2 SecurityList (35=y)	10
1.3.3 SecurityStatus (35=f)	15
1.3.4 MarketDataRequest (35=V)	17
1.3.5 MarketDataSnapshotFullRefresh (35=W)	18
1.3.6 MarketDataIncrementalRefresh (35=X)	22

Change Log

Date	Version	Description	Author
October 23 rd , 2023	1.0	- Initial version	IMKY
November 07 th , 2023	1.1	- Added messages Logon (35=A), Heartbeat (35=0), TestRequest (35=1), ResendRequest (35=2), Reject (35=3), SequenceReset (35=4) and Logout (35=5).	IMKY
November 27 th , 2023	1.2	- Added tag TradeCondition (277) in messages MarketDataSnapshotFullRefresh (35=W) and MarketDataIncrementalRefresh (35=X) - The valid value of tag SecurityType (167) has been changed from FEDERAL to GOVBOND	IMKY
February 19 th , 2024	1.3	- Added tag NoLotTypeRules (1234) in message SecurityList (35=y) - Added value 3 = CORPORATE in tag Product (460) - Added values CORP and CBIO in tag SecurityType (167) - Added values CBIO, CFF, CRA, CRI, DEB, LFT, LTN, NTN, NTNC and NTNFB in tag SecuritySubType (762)	IMKY
May 27 th , 2024	1.4	- Added optional tags in message SecurityList (35=y): <ul style="list-style-type: none"> MaxOrderQtyRfq (9746) MaxOrderQtyVoice (9747) AllowsFractionalQuantity (9750) AllowsNegativeTax (9751) - Added "Data Type" column to all tables - Values new and note added to the description of tag TradeCondition (277) <ul style="list-style-type: none"> RQF value – Indicate if new/cancel trade origin is RFQ Voice value – Indicate if new/cancel trade origin is Voice Note: Values 1, 2, 3 and x are reserved for future use. 	KYLC
August 16 th , 2024	1.5	- Added optional tags in message SecurityList (35=y): <ul style="list-style-type: none"> CouponPaymentDate (224) CouponRate (223) CouponType (1946) InstrAttribType (871) - Added optional tags in message MarketDataSnapshotFullRefresh (35=W): <ul style="list-style-type: none"> NetChgPrevDay (451) 	KYLC
February 14 th , 2025	1.6	- Added optional tag in message SecurityList (35=y): <ul style="list-style-type: none"> MinTaxIncrement (9600) 	KYLC
February 28 th , 2025	1.7	- Added optional tag in message SecurityList (35=y), MarketDataSnapshotFullRefresh (35=W) and MarketDataIncrementalRefresh (35=X): <ul style="list-style-type: none"> PriceType (423) - Added more values in optional tag InstrAttribType (871) in message SecurityList (35=y) and SecurityStatus (35=f).	KYLC
June 4 th , 2025	1.8	- Added more values in optional tag InstrAttribType (871) in message SecurityList (35=y) and SecurityStatus (35=f).	KYLC

		- Added more values in optional tag CouponType (1946) in message SecurityList (35=y).	
June 27 th , 2025	1.9	<p>- Added optional tag 326 (SecurityTradingStatus) in message SecurityList (35=y) and MarketDataIncrementalRefresh (35=X) and added more value in message MarketDataSnapshotFullRefresh (35=W) and SecurityStatus (35=f).</p> <p>- Added optional tag 876 (CPRRegType) in message SecurityList (35=y), SecurityStatus (35=f), MarketDataIncrementalRefresh (35=X) and MarketDataSnapshotFullRefresh (35=W).</p> <p>- Added optional tag 228 (Factor) in message SecurityList (35=y), SecurityStatus (35=f), MarketDataIncrementalRefresh (35=X) and MarketDataSnapshotFullRefresh (35=W).</p> <p>- Added optional tag 870 (NoInstrAttribs) and 872 (InstrAttribValue) in message SecurityList (35=y) and SecurityStatus (35=f) and editing value in optional tag 871 (InstrAttribType) in message SecurityList (35=y) and SecurityStatus (35=f).</p> <p>- Added optional tag 711 (NoUnderlyings), 311 (UnderlyingSymbol), 309 (UnderlyingSecurityID) and 305 (UnderlyingSecurityIDSource) in message SecurityList (35=y), SecurityStatus (35=f) and MarketDataSnapshotFullRefresh (35=W).</p> <p>- Added optional tag 286 (OpenCloseSettlFlag) in message MarketDataIncrementalRefresh (35=X).</p> <p>- Added optional tag 6939 (PriceBandType) in message MarketDataIncrementalRefresh (35=X).</p>	ACRSR KYLC
July 17 th , 2025	2.0	Added optional tag 274 (TickDirection), 451 (NetChgPrevDay), 1020 (TradeVolume), 37016 (MDInsertDate) and 37017 (MDInsertTime) in MarketDataIncrementalRefresh (35=X).	LDOG
August 7 th , 2025	2.1	Added more value in optional tag 326 (SecurityTradingStatus) in message SecurityList (35=y) and MarketDataIncrementalRefresh (35=X), MarketDataSnapshotFullRefresh (35=W) and SecurityStatus (35=f).	KYLC
November 4 th , 2025	2.2	Added a valid value 5 (Other) to CouponType	FGTCH
May 14 th , 2026	2.3	<p>This version introduces new tags to support the "Spread Over B" workflow.</p> <p>The tags related to spread and benchmark are only applicable to voice trades at this moment.</p> <p>Added optional tag 218 (Spread), tag 699 (BenchmarkSecurityID) in message MarketDataIncrementalRefresh (35=X) and MarketDataSnapshotFullRefresh (35=W).</p> <p>Added value in tag 6939 (PriceBandType) in message MarketDataSnapshotFullRefresh (35=W) and MarketDataIncrementalRefresh (35=X).</p> <p>Added comment in tag 270 (MDEntryPx) in message MarketDataSnapshotFullRefresh (35=W) and MarketDataIncrementalRefresh (35=X).</p> <p>Added value in tag 871 (InstrAttribType) in message SecurityList (35=y) and SecurityStatus (35=f).</p>	KYLC

1 Market Data FIX Message Specification

This section outlines the market data messages for fixed income securities as Brazilian Government Bonds and Corporate Bonds (future use). By implementing the specification in the document, clients will be able to process market data coming from Fixed Income Trading System.

The tag usage may vary depending on the market segment used (Brazilian Government Bonds – GOV and Corporate Fixed Income Bonds – CORP (for future use), this indicated by an “X” in the relevant columns at certain tables below. If a tag is marked as required (Req) but it’s not available in a given segment, it is deemed *not required* for that segment.

1.1 Message Blocks

This section contains “message blocks”, i.e. specific sets of tags that work as “stamps” in the message specification and are common to most or all market data messages.

1.1.1 Message Header (for all messages)

This section describes the header that is common to all messages of the market data feed.

Tag	Tag name	Req	Data Type	Comment
8	BeginString	Y	String	FIX4.4 (Must be the first field in the message)
9	BodyLength	Y	Length	(Must be the second field in the message)
35	MsgType	Y	String	(Must be the third field in the message)
1128	AppVerID	N	String	Specifies the service pack release being applied at message
49	SenderCompID	Y	String	The value used must be recognized and agreed by B3
56	TargetCompID	Y	String	Please use the value as provided
34	MsgSeqNum	Y	SeqNum	See standard FIX protocol specification
52	SendingTime	Y	UTCTimestamp	Indicates the time the message was sent by B3

1.1.2 Message Trailer (for all messages)

This section describes the trailer that is common to all messages of the market data feed.

Tag	Tag name	Req	Data Type	Comment
10	Checksum	Y	String	Always unencrypted, always last field in message

1.1.3 Instrument identification block

This block is common to most market data messages issued by B3. It contains the tags that uniquely identify an instrument and works as a “stamp” of the instrument identification in the message specification.

Tag	Tag name	Req	Data Type	Comment
48	SecurityID	N	String	Unique instrument identifier for a given qualifier
22	SecurityIDSource	N	String	SecurityID qualifier. Value issued by B3: 8 = Exchange Symbol (B3 security identification).
207	SecurityExchange	N	Exchange	Market to which the instrument belongs to.

1.2 Session Level Messages

1.2.1 Logon (35=A)

Tag	Tag Name	Req	Data Type	Comment
[Standard Message Header]				
98	EncryptMethod	Y	Integer	Must be "0"
108	HeartBtInt	Y	Integer	Recommended: "30"
141	ResetSeqNumFlag	N	Boolean	Indicates that both sides of the FIX session should reset sequence numbers.
553	Username	N	String	CAU username
554	Password	N	String	CAU Password
35002	CancelOnDisconnectType	N	Integer	Indicates whether orders should remain active on disconnection. Values valid: 0 – Doesn't cancel on disconnection 1 – Cancel on disconnection
35003	CancelOnDisconnectTimeoutWindow	N	Integer	Timeout in seconds to trigger cancellation after disconnection
[Standard Message Trailer]				

1.2.2 Logout (35=5)

Tag	Tag Name	Req	Data Type	Comment
[Standard Message Header]				
58	Text	Y	String	Explanation for Logout reason (if any).
[Standard Message Trailer]				

1.2.3 Heartbeat (35=0)

This message is sent over the instrument definition, snapshot recovery and incremental streams to notify customers that the multicast channel join was successful and that B3 will send the data when available.

There is no body for this message, only the standard header with tag 35=0.

1.2.4 TestRequest (35=1)

Tag	Tag Name	Req	Data Type	Comment
[Standard Message Header]				
112	TestReqID	Y	String	Identifier required for testing. Field included in the test request message to be returned without resulting flag
[Standard Message Trailer]				

1.2.5 ResendRequest (35=2)

Tag	Tag Name	Req	Data Type	Comment
[Standard Message Header]				
7	BeginSeqNo	Y	SeqNum	Message sequence number of first message in range to be resent
16	EndSeqNo	Y	SeqNum	Message sequence number of last message in range to be resent. If request is for a single message BeginSeqNo = EndSeqNo If request is for all messages subsequent to a particular message, EndSeqNo = 0 (representing infinity).
[Standard Message Trailer]				

1.2.6 Reject (35=3)

Tag	Tag Name	Req	Data Type	Comment
[Standard Message Header]				
45	RefSeqNum	Y	SeqNum	Message sequence number of first message in range to be resent
58	Text	N	String	Where possible, message to explain reason for rejection
371	RefTagID	N	Integer	The tag number of the FIX field being referenced.
372	RefMsgType	N	String	The MsgType of the FIX message being referenced.
373	SessionRejectReason	Y	Integer	Code to identify reason for a session-level <u>reject</u> message. Valid values: 0 = Invalid tag number 1 = Required tag missing 2 = Tag not defined for this message type 3 = Undefined Tag 4 = Tag specified without a value 5 = Value is incorrect (out of range) for this tag 6 = Incorrect data format for value 7 = Decryption problem 8 = Signature problem 9 = CompID problem 10 = Sending time accuracy problem 11 = Invalid MsgType 12 = XML Validation error 13 = Tag appears more than once 14 = Tag specified out of required order 15 = Repeating group fields out of order 16 = Incorrect NumInGroup count for repeating group 17 = Non "Data" value includes field delimiter (<SOH> character) 99 = Other
[Standard Message Trailer]				

1.2.7 SequenceReset (35=4)

Tag	Tag Name	Req	Data Type	Comment
[Standard Message Header]				

Tag	Tag Name	Req	Data Type	Comment
43	PossDupFlag	N	Boolean	Indicates possible retransmission of message with this sequence number Valid values: Y = Possible duplicate N = Original transmission
122	OrigSendingTime	N	UTCTimestamp	Original time of message transmission (always expressed in UTC) when transmitting orders as the result of a resend request.
123	GapFillFlag	N	Boolean	Indicates that the sequence reset message is replacing administrative or application messages which will not be resent. Valid values: Y = Gap fill message, MsgSeqNum field valid N = Sequence ignore MsgSeqNum
36	NewSeqNo	Y	SeqNum	New sequence number
[Standard Message Trailer]				

1.3 Application Messages

1.3.1 SecurityListRequest (35=x)

This message is used to retrieve a list of securities that are available for trading. Its response is a SecurityList message, which contains information about the instruments traded.

Tag	Tag name	Req	Data Type	Comment
[Standard Message Header]				
320	SecurityReqID	Y	String	Unique ID of the Security List Request. It's strongly recommended that this value is unique throughout the trading day since it will be used to cross reference the request to the response. When unsubscribing, this tag should contain the ID of the request being canceled.
263	SubscriptionRequestType	Y	Char	Subscribe or unsubscribe for security changes in the request. Values accepted by UMDf Conflated: 1 = Securities + Updates (Subscribe) 2 = Disable previous request (Unsubscribe)
460	Product	N	Integer	Specifies the Product of the desired instruments. (FILTER) Valid Values: 3 = CORPORATE 6 = GOVERNMENT
461	CFICode	N	String	Specifies the CFICode of the desired instruments. Please refer to ANNA CFI & ISO 10962 for details on how to use this field (https://anna-web.org/identifiers/#1629366848926-da25cf1b-d913)
[Standard Message Trailer]				

1.3.2 SecurityList (35=y)

This message is used to relay instrument information, such as insertion, update or deletion. Each message can contain multiple instruments and clients usually receive multiple messages in response to each request.

Tag	Tag name	Req	Data Type	Comment	
[Standard Message Header]					
320	SecurityReqID	C	String	Echoed back from the Security List Request message that caused this message to be sent. Always sent when this message is a reply to a Security List Request.	
322	SecurityResponseID	C	String	Unique ID of this message. Only sent when this message is a response to a Security List Request.	
560	SecurityRequestResult	C	Char	The results returned to the Security List Request message. Always sent when this message is a reply to a Security List Request. 0= Valid request 1 = Invalid or unsupported request 6 = Duplicate SecurityReqID M = Maximum number of subscriptions exceeded	
393	TotNoRelatedSym	C	Integer	Total number of securities being returned for this request. Always sent when this message is a reply to a Security List Request.	
893	LastFragment	C	Boolean	Indicates whether this message is the last in the sequence of messages requested. Not sent by default. Valid values: Y = Last message N = Not last message	
146	NoRelatedSym	C	NumInGroup	Specifies the number of repeating instruments specified. Not sent if this message is reporting an error (tag 560 > 0).	
→	55	Symbol	Y	String	Instrument Symbol.
→	48	SecurityID	Y	String	Unique instrument id.
→	22	SecurityIDSource	Y	String	Security ID qualifier.

→	207	SecurityExchange	Y	Exchange	Market to which the instrument belongs.	
→	1141	NoMDFeedTypes	N	NumInGroup	Number of MD Feed Types.	
→	→	1022	MDFeedType	N	String	Indicates feed type as standard or implied. Not sent for MBO. Valid values: STD = Standard MBP IMP = Implied MBP (not used)
→	→	264	MarketDepth	N	Integer	Identifies the number of depth levels of the book.
→	→	1021	MDBookType	N	Integer	Used to request a specific type of book updates when subscribing. If not sent means to subscribe for all available book types. Valid Values: 3 = Order Depth
→	454	NoSecurityAltID	C	NumInGroup	Number of alternate security identifiers.	
→	→	455	SecurityAltID	C	String	Security Alternate identifiers for this security.
→	→	456	SecurityAltIDSource	C	String	Identifies class or source of the SecurityAltID (455) value. Required if SecurityAltID is specified. 8= ExchangeSymbol 4= ISIN Number H= Clearing house/organization
→	460	Product	N	Integer	Indicates the type of product the security is associated with. Valid Values: 3 = CORPORATE 6 = GOVERNMENT	
→	461	CFICode	N	String	Classification of Financial Instruments (CFI code) values, which indicate the type of security using ISO 10962 standard.	
→	167	SecurityType	N	String	Indicates the type of the security. Valid Values (Corporate fixed income) - CBIO - CORP Valid Values (Government bond) - GOVBOND	

→	762	SecuritySubType	N	String	The sub type of the instrument. Values valid: 1 = CBIO 2 = CFF 3 = CRA 4 = CRI 5 = DEB 6 = LFT 7 = LTN 8 = NTNB 9 = NTNC 10 = NTNF
→	541	MaturityDate	C	LocalMktDate	Date of instrument maturity. For all but Spot and Forwards.
→	224	CouponPaymentDate	N	LocalMktDate	Date interest is to be paid. Used in identifying Corporate Bond issues.
→	225	IssueDate	N	LocalMktDate	The date on which the security is issued/activated.
→	228	Factor	N	Float	Used only for Casada instruments. It represents the Hedge Factor that exists on the Quotes screen.
→	223	CouponRate	N	Percentage	The rate of interest provides the currency amount of the periodic interest payment.
→	1946	CouponType	N	Integer	The coupon type of a bond Values valid: 1 = FIXED_RATE 2 = FLOATING_RATE 3 = STRUCTURED 4 = ZERO 5 = OTHER
→	326	SecurityTradingStatus	N	Integer	Identifier for the security trading status. Conditionally required when MDEntryType='c'. If absent the default value is 17 = Open. Valid Values: 17 = Ready to trade (start of session) 21 = Pre-Open 2 = Trading Halt 18 = Not available for trading
→	470	CountryOfIssue	N	Country	ISO country code of instrument issue.
→	107	SecurityDesc	N	String	Descriptive string of the security.

→	876	CRegType	N	String	The registration type of a commercial paper issuance Valid values: 1 = Automatic 2 = Manual
→	980	SecurityUpdateAction	Y	Char (String)	When sent as a request response will always carry "M". Valid values: A = Add D = Delete M = Modify
→	969	MinPriceIncrement	N	Float	Number of minimum tick increments.
→	9600	MinTaxIncrement	N	Float	Number of minimum tax increments.
→	9746	MaxOrderQtyRfq	N	Qty	Maximum quantity rfq of an order for the security.
→	9747	MaxOrderQtyVoice	N	Qty	Maximum quantity voice of an order for the security.
→	9748	MaxOrderQty	N	Qty	Maximum quantity of an order for the security.
→	9749	MinOrderQty	N	Qty	Minimum quantity of an order for the security.
→	9750	AllowsFractionalQuantity	N	Boolean	Indicates whether the security accepts decimal values.
→	9751	AllowsNegativeTax	N	Boolean	Indicates whether the rate/price value can be negative.
	870	NoInstrAttrib	N	NumInGroup	Number of repeating InstrAttribType entries.
→	871	InstrAttribType	N	Integer	Code to represent the type of instrument attribute. Valid values: 8 = COUPON_PERIOD 15 = IN_DEFAULT 50 = IS_RESTRICTED_EFFORT 51 = Rating Fitch 52 = CUSTOM_INTERNAL_ATTRIBUTE_02

					53 = Rating SP 54 = TRADING_DEAD_LINE 55 = PRIVATE_BOOK_DESK_OWNER 56 = PRIVATE_BOOK_ID 57 = IS_TAKER 58 = TRADING_SECTOR_ID 59 = SPREAD_OVER_B_ENABLED
→	872	InstrAttribValue	N	String	Attribute value appropriate to the InstrAttribType (871) field. Valid values for 871 = 15, 50, 55, 56 0 = No 1 = Yes Valid values for 871 = 58 2 = Casada NTNB 3 = Short-Term Standard Lot NTNB 4 = Long-Term Standard Lot NTNB 5 = Standard Lot LTN 6 = Standard Lot NTNF 7 = Standard Lot LFT 8 = Standard Lot NTNC 9 = Fractional LFT 10 = Fractional NTNC 11 = Fractional LTN 12 = Fractional NTNF 13 = Short-Term Fractional NTNB 14 = Long-Term Fractional NTNB 15 = Casada LTN 16 = Casada NTNF 17 = CBIO 18 = CFF 19 = CRA 20 = CRI 21 = DEB
	711	NoUnderlyings	N	NumInGroup	Used only for Casada instruments. Number of underlying legs that make up the security.
→	311	UnderlyingSymbol	N	String	Used only for Casada instruments. Underlying instrument's ticker symbol.
→	309	UnderlyingSecurityID	N	String	Used only for Casada instruments. Underlying instrument's security identifier.
→	305	UnderlyingSecurityIDSource	N	String	Used only for Casada instruments. Qualifier for underlying instrument's security identifier. 8 = Exchange Symbol (BVMF security identification).

→	15	Currency	N	Currency	Currency used for the price.	
→	6937	Asset	N	String	Asset associated with the security, such as DOL, BGI, OZ1, WDL, CNI, etc.	
→	6938	SecurityValidityTimestamp	N	UTCTimestamp	Indicates the UTC timestamp when trading for this security expires, i.e. when it is not eligible to trade anymore.	
→	561	RoundLot	N	Qty	The trading lot size of the security.	
→	423	PriceType	N	Integer	Indicates the type of price Valid values: 1 = Percentage 2 = Per_Unit 6 = Spread 9 = Yield	
→	1234	NoLotTypeRules	N	Integer	Rules defining lot size.	
→	→	1093	LotType	N	Integer	Defines the lot type for the instruments. Valid Values: 1 = Odd Lot 2 = Round Lot
[Standard Message Trailer]						

1.3.3 SecurityStatus (35=f)

The Security Status message relays trading phase changes of a specific instrument or instrument group.

Tag	Tag name	Req	Data Type	Comment
[Standard Message Header]				
[Instrument identification block]				
See Section "Instrument Identification Block" for tag values				
228	Factor	N	Float	Used only for Casada instruments. It represents the Hedge Factor that exists on the Quotes screen.
876	CPRegType	N	String	The registration type of a commercial paper issuance Valid values: 1 = Automatic 2 = Manual
870	NoInstrAttrib	N	NumInGroup	Number of repeating InstrAttribType entries.

Tag		Tag name	Req	Data Type	Comment
→	871	InstrAttribType	N	Integer	Code to represent the type of instrument attribute. Valid values: 8 = COUPON_PERIOD 15 = IN_DEFAULT 50 = IS_RESTRICTED_EFFORT 51 = Rating Fitch 52 = CUSTOM_INTERNAL_ATTRIBUTE_02 53 = Rating SP 54 = TRADING_DEAD_LINE 55 = PRIVATE_BOOK_DESK_OWNER 56 = PRIVATE_BOOK_ID 57 = IS_TAKER 58 = TRADING_SECTOR_ID 59 = SPREAD_OVER_B_ENABLED
→	872	InstrAttribValue	N	String	Attribute value appropriate to the InstrAttribType (871) field. Valid values for 871 = 15, 50, 55, 56 0 = No 1 = Yes Valid values for 871 = 58 2 = Casada NTNB 3 = Short-Term Standard Lot NTNB 4 = Long-Term Standard Lot NTNB 5 = Standard Lot LTN 6 = Standard Lot NTNF 7 = Standard Lot LFT 8 = Standard Lot NTNC 9 = Fractional LFT 10 = Fractional NTNC 11 = Fractional LTN 12 = Fractional NTNF 13 = Short-Term Fractional NTNB 14 = Long-Term Fractional NTNB 15 = Casada LTN 16 = Casada NTNF 17 = CBIO 18 = CFF 19 = CRA 20 = CRI 21 = DEB

Tag	Tag name	Req	Data Type	Comment	
711	NoUnderlyings	N	NumInGroup	Used only for Casada instruments. Number of underlying legs that make up the security.	
→	311	UnderlyingSymbol	N	String	Used only for Casada instruments. Underlying instrument's ticker symbol.
→	309	UnderlyingSecurityID	N	String	Used only for Casada instruments. Underlying instrument's security identifier.
→	305	UnderlyingSecurityIDSource	N	String	Used only for Casada instruments. Qualifier for underlying instrument's security identifier. 8 = Exchange Symbol (BVMF security identification).
60	TransactTime	Y	UTCTimestamp	Timestamp when the business transaction represented by the message occurred.	
75	TradeDate	Y	LocalMktDate	Trade date of the Market Data messages.	
336	TradingSessionID	N	String	Identifier for Trading Session. Valid values: 1 = Day	
342	TradSesOpenTime	N	UTCTimestamp	Indicates the time the auction is scheduled to end.	
326	SecurityTradingStatus	N	Integer	Identifier for the security trading status. Conditionally required when MDEntryType='c'. If absent the default value is 17 = Open. Valid Values: 17 = Ready to trade (start of session) 21 = Pre-Open 2 = Trading Halt 18 = Not available for trading	
1500	MDStreamID	N	String	The identifier or the name of the market data stream. If missing, default=E. Valid values: E = electronic	
[Standard Message Trailer]					

1.3.4 MarketDataRequest (35=V)

A Market Data Request is a general request for market data for tradable securities. A successful Market Data Request is

replied by a single Market Data Full Snapshot message for each instrument that matches the request. Upon receiving one of such messages, incremental updates (Market Data Incremental Refresh messages) start being generated for instruments whose snapshots have been already received.

Tag	Tag name	Req	Data Type	Comment
[Standard Message Header]				
262	MDReqID	Y	String	Must be unique, or the ID of previous Market Data Request to disable if SubscriptionRequestType = Disable previous Request (2).
263	SubscriptionRequestType	Y	Char	Indicates what type of response is expected. Valid values: 1 = Snapshot + Updates (Subscribe) 2 = Disable previous Request (Unsubscribe)
460	Product	N	Integer	Indicates the type of product the security is associated with. (FILTER) 3 = CORPORATE 6 = GOVERNMENT
[Standard Message Trailer]				

1.3.5 MarketDataSnapshotFullRefresh (35=W)

The Market Data Snapshot/Full Refresh messages are sent as the response to a Market Data Request message. The message refers to only one Market Data Request. It will contain the appropriate MDReqID tag value to correlate the request with the response.

Tag	Tag name	Req	Data Type	Comment	
[Standard Message Header]					
262	MDReqID	Y	String	Echoed back from the Market Data Request message.	
75	TradeDate	N	LocalMktDate	Used to specify the trading date which a set of market data applies for, in YYYYMMDD format. Absence of this field indicates current day (expressed in local time in the place of trade).	
911	TotNumReports	N	Integer	Total number of snapshots to be returned.	
893	LastFragment	N	Boolean	Indicates whether this message is the last in the sequence of messages requested. Not sent by default. Valid values: Y = Last message N = Not last message	
→	48	SecurityID	N	String	Unique instrument id.
→	22	SecurityIDSource	N	String	Security ID qualifier.
→	207	SecurityExchange	N	Exchange	Market to which the instrument belongs.
→	228	Factor	N	Float	Used only for Casada instruments. It represents the Hedge Factor that exists on the Quotes screen.
→	876	CPRRegType	N	String	The registration type of a commercial paper issuance Valid values: 1 = Automatic

Tag	Tag name	Req	Data Type	Comment
				2 = Manual
711	NoUnderlyings	N	NumInGroup	Used only for Casada instruments. Number of underlying legs that make up the security.
→ 311	UnderlyingSymbol	N	String	Used only for Casada instruments. Underlying instrument's ticker symbol.
→ 309	UnderlyingSecurityID	N	String	Used only for Casada instruments. Underlying instrument's security identifier.
→ 305	UnderlyingSecurityIDSource	N	String	Used only for Casada instruments. Qualifier for underlying instrument's security identifier. 8 = Exchange Symbol (BVMF security identification).
268	NoMDEntries	Y	NumInGroup	Number of entries following.
→ 269	MDEntryType	Y	Char	Type Market Data entry. Valid values: 0 = Bid 1 = Offer 2 = Trade 4 = Opening Price 5 = Closing Price 7 = Trading Session High Price 8 = Trading Session Low Price 9 = Trading Session VWAP Price g = Price Band B = Trade Volume c = Security trading state/ phase
→ 423	PriceType	N	Integer	Indicates the type of price Valid values: 1 = Percentage 2 = Per_Unit 6 = Spread 9 = Yield
→ 270	MDEntryPx	C	Price	Price of the MD entry. Conditionally required if the MD entry relates to a price. For Voice Spread Over B, it will only be included after the reference B rate has been provided.
→ 271	MDEntrySize	C	Qty	Quantity represented by the Market Data Entry. Conditionally required when MDEntryType = Bid (0), Offer (1), Trade (2) or Opening Price (4).
→ 272	MDEntryDate	Y	UTCDateOnly	Date of Market Data Entry.
→ 273	MDEntryTime	Y	UTCDateOnly	Time of Market Data Entry, up to milliseconds (hhmmssSSS).

Tag	Tag name	Req	Data Type	Comment	
→	274	TickDirection	C	Char	Direction of the price tick. Conditionally required if reporting a Trade. Valid values: 0 = Plus Tick 1 = Zero-Plus Tick 2 = Minus Tick 3 = Zero-Minus Tick
→	37	OrderID	C	String	Unique identifier for Order as assigned by the exchange, maps to the SecondaryOrderID field in the Execution Report message for the derivatives market (for the FX market, it is the actual OrderID). Required for Bids or Offers for market by order.
→	286	OpenCloseSettlFlag	N	MultipleValueString	Identifies if the opening price in field MDEntryPx represents a theoretical opening price and applicable to describe when the settlement data are related to. Valid values: 0 = Daily Open / Close / Settlement entry 4 = Entry from previous business day 5 = Theoretical Price value
→	290	MDEntryPositionNo	N	Integer	Display the position of a bid or offer, numbered from the most competitive to the least competitive, per market side, beginning with 1. Conditionally required when MDEntryType = 0 or 1 (Bid or offer)
→	326	SecurityTradingStatus	N	Integer	Identifier for the security trading status. Conditionally required when MDEntryType='c'. If absent the default value is 17 = Open. Valid Values: 17 = Ready to trade (start of session) 21 = Pre-Open 2 = Trading Halt 18 = Not available for trading
→	336	TradingSessionID	N	String	Used to mark NonRegular Session trades. If it is not present the default value is "1" (Regular Day Session). Valid values: 1 = Day
	451	NetChgPrevDay	C	PriceOffset	Net change from previous trading day's closing price vs. last traded price (offshore currency)

Tag	Tag name	Req	Data Type	Comment
→	277 TradeCondition	N	MultipleValueString	<p>For optional use in reporting Trades/Imbalance. Space delimited list of conditions describing a trade/imbalance.</p> <p>Valid values:</p> <ul style="list-style-type: none"> 1 – Leg Trade 2 – Marketplace entered trade (trade on behalf) 3 – Multi asset Trade L – Last Trade at the same price indicator (price same as last) P – Imbalance more buyers (auction, more buyers) Q – Imbalance more sellers (auction, more sellers) R – Opening Price U – Exchange Last (last price) X – Crossed AW – Last auction price (theoretical auction close price) AWR – Opening and auction price (theoretical auction price and opening of the paper - 1st deal generated auction) RFQ – Indicate if new/cancel trade origin is RFQ VO – Indicate if new/cancel trade origin is Voice <p>Note: Values 1, 2, 3 and x are reserved for future use.</p>
→	1003 TradeID	C	String	Contains the unique identifier for this trade per instrument + trading date, as assigned by the exchange. Required if reporting a Trade.
→	1020 TradeVolume	N	Qty	Total traded quantity (shares/contracts) of the trading day. It could be present only in the Trade (269=2) and Trade Volume (269=B) blocks.
→	6939 PriceBandType	N	Integer	<p>Indicates type of price banding.</p> <p>Valid Values:</p> <ul style="list-style-type: none"> 1= Hard Limits 2= Auction Limits 3= Rejection Band 4= Static Limits 5= Spread Over B Limits
→	1148 LowLimitPrice	N	Price	Allowable low limit price for the trading day. A key parameter in validating order price. Used as the lower band for validating order prices. Orders submitted with prices below the lower limit will be rejected.
→	1149 HighLimitPrice	N	Price	Allowable high limit price for the trading day. A key parameter in validating order price. Used as the upper band for validating order prices. Orders submitted with prices above the upper limit will be rejected.

Tag	Tag name	Req	Data Type	Comment
→	1500 MDStreamID	N	String	The identifier or the name of the market data stream. If missing, default=E. Valid values: E = electronic
218	Spread	N	PriceOffset	Basis points relative to a benchmark. To be expressed as "count of basis points" (vs. an absolute value).
699	BenchmarkSecurityID	C	String (12)	The identifier of the benchmark security. This field must be present if tag 218 (Spread) is specified. Otherwise, it must not be sent.
[Standard Message Trailer]				

1.3.6 MarketDataIncrementalRefresh (35=X)

After a subscription for Market Data messages succeeded and the Market Data Snapshot/Full Refresh has been issued, further updates will be communicated to the subscriber via the Market Data Incremental Refresh message. These messages will be sent until the client institution cancels the subscription with a Market Data Request with SubscriptionRequestType=2.

Tag	Tag Name	Req	Data Type	Comment
[Standard Message Header]				
75	TradeDate	N	LocalMktDate	Used to specify the trading date which a set of market data applies for, in YYYYMMDD format. Absence of this field indicates the current day (expressed in the local time of the place of the trade).
268	NoMDEntries	Y	NumInGroup	Number of entries following.
→	279 MDUpdateAction	Y	Char	Type of Market Data update action. Valid values: 0 = New 1 = Change 2 = Delete
→	37 OrderID	C	String	Unique identifier for Order as assigned by the exchange, maps to the SecondaryOrderID field in the Execution Report message for the derivatives market (for the FX market, it is the actual OrderID). Required for Bids or Offers for market by order.

Tag	Tag Name	Req	Data Type	Comment	
→	269	MDEntryType	Y	Char	Type Market Data entry. Valid values: 0 = Bid 1 = Offer 2 = Trade 4 = Opening Price 5 = Closing Price 7 = Trading Session High Price 8 = Trading Session Low Price 9 = Trading Session VWAP Price g = Price Band B = Trade Volume c = Security trading state/ phase
→	876	CPRegType	N	String	The registration type of a commercial paper issuance Valid values: 1 = Automatic 2 = Manual
→	423	PriceType	N	Integer	Indicates the type of price Valid values: 1 = Percentage 2 = Per_Unit 6 = Spread 9 = Yield
→	48	SecurityID	N	String	Unique instrument id.
→	22	SecurityIDSource	N	String	Security ID qualifier.
→	207	SecurityExchange	N	Exchange	Market to which the instrument belongs.
→	270	MDEntryPx	C	Price	Price of the Market Data Entry. Required when this market data entry involves a price. Represents the notional value for trade volume (B). Other entry types that do not involve price do not require this tag. For Voice Spread Over B, it will only be included after the reference B rate has been provided.

Tag	Tag Name	Req	Data Type	Comment	
→	271	MDEntrySize	C	Qty	Quantity or volume represented by the Market Data Entry. Required when MDUpdateAction = New (0) and MDEntryType = Bid (0), Offer (1), Trade (2), Trade Volume (B) or Opening Price (4).
→	272	MDEntryDate	Y	UTCDateOnly	Date of Market Data Entry.
→	273	MDEntryTime	Y	UTCDateOnly	Time of Market Data Entry, up to milliseconds (hhmmssSSS).
→	286	OpenCloseSettlFlag	N	MultipleValueString	Identifies if the opening price in field MDEntryPx represents a theoretical opening price and applicable to describe when the settlement data are related to. Valid values: 0 = Daily Open / Close / Settlement entry 4 = Entry from previous business day 5 = Theoretical Price value
→	277	TradeCondition	N	MultipleValueString	For optional use in reporting Trades/Imbalance. Space delimited list of conditions describing a trade/imbalance. Valid values: 1 – Leg Trade 2 – Marketplace entered trade (trade on behalf) 3 – Multi asset Trade L – Last Trade at the same price indicator (price same as last) P – Imbalance more buyers (auction, more buyers) Q – Imbalance more sellers (auction, more sellers) R – Opening Price U – Exchange Last (last price) X – Crossed AW – Last auction price (theoretical auction close price) AWR – Opening and auction price (theoretical auction price and opening of the paper - 1st deal generated auction) RFQ – Indicate if new/cancel trade origin is RFQ VO – Indicate if new/cancel trade origin is Voice Note: Values 1, 2, 3 and x are reserved for future use.
→	290	MDEntryPositionNo	N	Integer	Display the position of a bid or offer, numbered from the most competitive to the least competitive, per market side, beginning with 1. Conditionally required when MDEntryType = 0 or 1 (Bid or offer)
→	1003	TradeID	C	String	Contains the unique identifier for this trade per instrument + trading date, as assigned by the exchange. Conditionally required if reporting a Trade.
→	326	SecurityTradingStatus	N	Integer	Identifier for the security trading status. Conditionally required when MDEntryType='c'. If

Tag	Tag Name	Req	Data Type	Comment	
				absent the default value is 17 = Open. Valid Values: 17 = Ready to trade (start of session) 21 = Pre-Open 2 = Trading Halt 18 = Not available for trading	
→	1148	LowLimitPrice	N	Price	Allowable low limit price for the trading day. A key parameter in validating order price. Used as the lower band for validating order prices. Orders submitted with prices below the lower limit will be rejected.
→	6939	PriceBandType	N	Integer	Indicates type of price banding. Valid Values: 1= Hard Limits 2= Auction Limits 3= Rejection Band 4= Static Limits 5= Spread Over B Limits
→	1149	HighLimitPrice	N	Price	Allowable high limit price for the trading day. A key parameter in validating order price. Used as the upper band for validating order prices. Orders submitted with prices above the upper limit will be rejected.
→	1500	MdStreamID	N	String	The identifier or the name of the market data stream. If missing, default=E. Valid values: E = electronic
→	274	TickDirection	C	Char	Direction of the price tick. Conditionally required if reporting a Trade. Valid values: 0 = Plus Tick 1 = Zero-Plus Tick 2 = Minus Tick 3 = Zero-Minus Tick
→	451	NetChgPrevDay	C	PriceOffset	Net change from previous trading day's closing price vs. last traded price (offshore currency).
→	1020	TradeVolume	N	Qty	Total traded quantity (shares/contracts) of the trading day. It could be present only in the Trade (269=2) and Trade Volume (269=B) blocks.
→	37016	MdInsertDate	N	UTCDateOnly	Date when the order was inserted ou re-inserted into the order book. In Trade (269=2 - New or Delete) - original trade date or manually entered by MktOps.
→	37017	MdInsertTime	N	UTCTimeOnly	Time when the order was inserted ou re-inserted into the order book or manually altered by by MktOps. This tag now includes up to milliseconds (hhmmssSSS).

Tag	Tag Name	Req	Data Type	Comment
218	Spread	N	PriceOffset	Basis points relative to a benchmark. To be expressed as "count of basis points" (vs. an absolute value).
699	BenchmarkSecurityID	C	String (12)	The identifier of the benchmark security. This field must be present if tag 218 (Spread) is specified. Otherwise, it must not be sent.
[Standard Message Trailer]				